



# 3036E

Compact Utility Tractor



JOHN DEERE



# Specifications

Engine	
Aspiration	Naturally Aspirated
No. of Cylinders	3
Displacement (liter)	1.642
Rated Power (hp)	34.8
Rated Engine Speed (rpm)	2800
Fuel Tank Capacity (liter)	38.5
Cooling Package	Coolant cooled with overflow reservoir
Air Filter	Dry type, Dual elements
Transmission	
Gears	SyncReverser, 8 Forward + 8 Reverse
Clutch	Single Dry traction Clutch
Power Take Off (PTO)	
PTO Speed (r/min)	540 @ 2500 ERPM, 540E @ 1925 ERPM
PTO Power (hp)	28.5

Hydraulic	
Type	Open Center
Hydraulic Lift at Hitch Balls (kg)	910
Hitch Category	CAT I
Steering & Brake	
Type of Steering	Power Steering
Type of Brake	Oil Immersed Disc Brake
Electrical	
Battery	12 V, 52 Ah
Alternator	12 V, 43 Amp
Starter	12 V, 1.2 kW
Wheels & Tires	
Front Tire	8.0 x 16, 4 PR
Rear Tire	12.4 X 24, 4 PR, High lug depth (HLD)

Dimensions & Weight	
Total Weight (kg)	1263
Wheel Base (mm)	1574
Overall Length - without Front Weight (mm)	2919
Overall Width (mm)	1455
Over Height (mm)	2105
Ground Clearance (mm)	388
Turning Radius with Brake / without Brake (mm)	2600 / 2800
Rear Track Width (mm)	1130



For more information, please contact our authorized dealer.



John Deere Genuine Parts  
| Economical | Reliable | Easily Available |

[www.JohnDeere.com](http://www.JohnDeere.com)

This literature has been compiled for broad circulation in Southeast Asia. While general information, pictures and descriptions are provided, some illustrations and text may include finance product options and accessories not available in all regions. Please contact your local dealer for details. John Deere reserves the right to change specification and design of products described in this literature without notice. The green and yellow color scheme, the leaping deer logo and the JOHN DEERE word mark are trademarks of Deere & Company.